

### For Earth, For Life



# B3350SU Special Utility Tractor

The new B3350SU tractor with a powerful diesel engine brings comfort to a variety of task handling jobs.

## Our most powerful B-Series tractor ever combines user-friendly operation and versatility with a wide variety of implements.

#### **Diesel Engine**

The B3350SU's liquid-cooled E-TVCS (Emission-Three Vortex Combustion System) diesel engine delivers 33HP (27 PTO HP) with high torque for the tractor strength you need, combined with reduced emissions. The B3350SU's Diesel Particulate Filter (DPF) Muffler is compliant with the latest Tier IV emission regulations.

#### **3-Range Transmission**

Our proven hydrostatic transmission provides the B3350SU with powerful and smooth shifting performance for heavy-duty loader applications. Range gears can be set between Low, Mid, and High to match a variety of operations.



#### 3-Point Hitch

The capable PTO horsepower and a Powerful Category I 3-point hitch ensures easy attaching and detaching of implements, such as a rotary cutter, box blade and finishing mower. The intuitive clutch-less PTO engagement simplifies operation.





#### **Specifications**

Model		B3350SUHSD
Engine		
Туре		E-TVCS, liquid cooled, 4-cylinder diesel
Make, Model		V1505-T-E4-D26-R
PTO horsepower	HP (kW)	27.0 (20.1)
Engine gross horsepower*	HP (kW)	33.0 (24.6)
Rated RPM	rpm	2500
Bore and stroke	in. (mm)	3.1 × 3.1 (78 × 78.4)
Displacement	cu. in. (cc)	91.5 (1498)
Air cleaner	cu. III. (cc)	4.5 inch Dual paper element
Lubrication		Forced lubrication
Cooling system		Pressurized radiator
Radiator fan		Radial air flow
		Hadiai ali now
Capacities	and (4)	7.2 /07.5\
Fuel tank	gal (ℓ)	7.3 (27.5)
Cooling system	qts. (ℓ)	4.5 (4.3)
Engine oil	qts. (ℓ)	5.1 (4.8)
Transmission case	gal (ℓ)	4.0 (15)
Drive train Clutch		N / A
Transmission		HST (3 ranges)
Differential lock		· · · · · · · · · · · · · · · · · · ·
		Standard
Final drive Brake		Spur gear  Multi-plate wet disc
		Multi-plate wet disc
Type		Independent
Rear	rpm	540
Hydraulics	i piii	
Type		Open center
Pump		Dual pump
Total pump output	gpm (ℓ/min.)	8.7 (33.1)
Hydraulic outlet	01 ( ,	Rear outlet
3-point hitch		Category I
Hydraulic control system		Quarter inching valve
Lift capacity at lift point	lbs. (kg)	2139 (970)
24" behind LP	lbs. (kg)	1676 (760)
Steering		Hydraulic power steering
Standard tire size		- I yanaano porior otooning
Front (Farm)		7-12
Rear (Farm)		12.4 -16
Traveling speeds (at rated engine r	rpm)	
Forward	mph (km/h)	0-14.3 (0-23.0)
Reverse	mph (km/h)	0-11.4 (0-18.4)
Dimensions		
Overall length (w/o 3P)	in. (mm)	101.2 (2570)
Overall width (min. tread)	in. (mm)	53.7 (1365)
Overall height	in. (mm)	78.5 (1995)
Wheelbase	in. (mm)	65.6 (1666)
Ground clearance	in. (mm)	14.6 (370)
Turning radius with brake	feet (m)	6.9 (2.1)
Weight	lbs. (kg)	1874 (850)
Other Features		Coil spring suspension seat, Drawbar, Tool box, 12V Power socket

<sup>\*</sup>SAE J1995

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only.

Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.

©2013 Kubota Corporation



#### **KUBOTA TRACTOR CORPORATION**

Kubota Tractor Corporation, 3401 Del Amo Boulevard, Torrance CA 90503 Western Division: 1175 S. Guild Ave., Lodi, CA 95240 Tel (209) 334-9910 Central Division: 14855 FAA Boulevard, Fort Worth, TX 76155 Tel (817) 571-0900 Northern Division: 6300 at One Kubota Way, Groveport, OH 43125 Tel (614) 835-1100 Southeast Division: 1025 Northbrook Parkway, Suwanee, GA 30024 Tel (770) 995-8855

